

Specifications Model: CB71

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.9-inch 1080p Progressive Scan CMOS sensor
	Minimum Illumination	0.3-0.5Lux(color mode), 0 Lux(B&W mode)
	Lens	3.2mm module
	View Angle	145°(Diagonal)
	Night vision	Automatic lens sensing switch, 6pcs 940nm SMD IR LED, IR irradiation distance:5-10 m
Video	Encode format	H.264+/H.264 main profile/Motion-JPEG/JPEG
	Streams	Main stream: 1080p(1920×1080)@30fps Substream: 360p(640×360)@15fps
	Bit Rate/Max Fps	128~4096kbps/30pfs
	Image adjustment	Brightness and contrast can be adjusted
	Encode format	H.264+/H.264 main profile/Motion-JPEG/JPEG
Audio	Input	Built-in -38db microphone
	Output	8 Ω 0.5W speaker
	Sampling frequency /Bit width	8KHz/16bit
	Compression standard /code rate	ADPCM/32kbps
Network	Ethernet	N/A (connect via AP hotpot mode)
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,P2P etc
	Wireless LAN	IEEE802.11b/g/n, Supports AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 256GB, cloud storage
Alarm	Alarm Trigger	PIR detection
Physical Environmental	Rated voltage	DC5V±5%
	Power supply	Built-in 1500mAh batteries
	Power consumption	Rated power: 2.05W (with infrared lights on) Maximum power: 3.0W(All function on)/Standby power:0.002W
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: 60g Gross: 210g(Note: in kind prevail)
	Package size	133x104x60mm (L×W×H)